

Features:

- ◆ Metal IR Dome IP Camera
- ◆ IR LED: \varnothing 5 X 36 pcs, IR Range: 30M
- ◆ Video Output: 1 x RJ45 port, wifi Optional
- ◆ Support Onvif, Support Gmail/GOOGLE/QQ/EMAIL
- ◆ PNP(Plug and Play), support smart phone & tablets
- ◆ OSD, Motion Detection, Remote View and Control, IR-Cut
- ◆ Working Temperature: $-10^{\circ}\text{C} \sim +60^{\circ}\text{C}$
- ◆ Size: 140mm x 95mm
- ◆ Weight: 1000g



Specifications

Model ID	VN-IKV10	VN-IKV13E	VN-IKV13	VN-IKV20C	VN-IKV20	VN-IKV20A	VN-IKV20H	VN-IKV40
Description	Metal IR Dome IP Camera,IR LED: \varnothing 5 X 36 pcs, IR Range: 30M							
TV System	NTSC / PAL							
Video Output	1 x RJ45 port							
Chipset Solution	1/4" OV 9712+HI3518E 1.0 Mega Pixels CMOS	1/3" Aptina AR0130 + HI3518E 1.3 Mega Pixels CMOS	1/3" Aptina AR0130 + HI3518C 1.3 Mega Pixels CMOS	1/3" XM SC2035 + HI3516C 2 Mega Pixels CMOS	1/2.5" Sony IMX323 + HI3516C 2 Mega Pixels CMOS	1/2.5" Sony IMX323 + HI3516C 2 Mega Pixels CMOS	1/3" Aptina AR0237 + HI3516D 2 Mega Pixels CMOS	1/3" OV4689 + HI3516D 4MP HD CMOS Sensor
Resolution	720P@ 25fps(PAL), 30fps(NTSC)	960P @ 25fps(PAL), 30fps(NTSC)	960P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	4MP @ 15fps(PAL), 15fps(NTSC)
Effective Pixels	1920(H) \times 720(V)	1920(H) \times 960(V)	1920(H) \times 960(V)	1920(H) \times 1080(V)	1920(H) \times 1080(V)	1920(H) \times 1080(V)	1920(H) \times 1080(V)	2592(H) \times 1520(V)
Minimum Illumination	0.001Lux							
Lens	2MP 2.8-12mm Manual Zoom Lens	2MP 2.8-12mm Manual Zoom Lens	2MP 2.8-12mm Manual Zoom Lens	2MP 2.8-12mm Manual Zoom Lens	2MP 2.8-12mm Manual Zoom Lens	3MP 2.8-12mm motorized zoom lens	2MP 2.8-12mm Manual Zoom Lens	2MP 2.8-12mm Manual Zoom Lens
Sync,System	Internal Synchronization							
Network	1 RJ45 Ethernet interface, 10/100M adaptation							
Video Compression	H.264 compression						H.265 compression	
Protocol	Support Gmail/GOOGLE/QQ/EMAIL							
Onvif	Support Onvif							
S/N Ratio	\geq 58dB							
POE	Optional							
OSD	YES							
WIFI	/	/	Optional	/	Optional	Optional	Optional	Optional
Power Source	DC 12V/2A							
Consumption	<5W							
Operating Enviroment	$-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ / 10% ~ 95%RH							
Working Humidity	\leq 90%							
Size(mm)	140mm x 95mm							
Weight(kg)	1.0 kg							