Features:

- ◆ Metal IR Dome IP Camera
- ◆ IR LED: ¢ 5 X 24 pcs, IR Range: 20M
- ◆ Video Output: 1 x RJ45 port
- ◆ Support Onvif, Support Gmail/GOOGLE/QQ/EMAIL
- ◆ PNP(Plug and Play), support smart phone & tablets
- ◆ OSD, Motion Detection, Remote View and Control, IR-Cut
- ◆ Working Temperature: -10℃~ +60℃
- ◆ Size: 94mm x 69mm
- ◆ Weight: 0.48KG

Specifications

Model ID	VN-IAB10H	VN-IAB13E	VN-IAB20	VN-IAB20F
Description	Metal IR Dome IP Camera, IR Led: ¢ 5 X 24 pcs, IR Range: 20M			
TV System	NTSC / PAL			
Video Output	1 x RJ45 port			
Chipset Solution	1/4" XM H42 + Hi3518E 1.0 Mega Pixels CMOS	1/3" Aptina AR0130 + Hi3518EV200 1.3 Mega Pixels CMOS	1/2.5" Sony IMX323 + Hi3516CV200 2 Mega Pixels CMOS	1/3" F22 + Hi3516CV300 2 Mega Pixels CMOS
Resolution	720P@ 25fps(PAL), 30fps(NTSC)	960P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	1080 @ 25fps(PAL), 30fps(NTSC)
Effective Pixels	1920(H)×720(V)	1920(H)×960(V)	1920(H)×1080(V)	1920(H)×1080(V)
Minimum Illumination	0.001Lux			
Lens	3.6mm Board Lens			
	/	2.8/6/8mm (Optional)	2.8/6/8mm (Optional)	/
Sync,System	Internal Synchronization			
Network	1 RJ45 Ethernet interface, 10/100M adaptation			
Video Compression	H.264 compression			H.265 compression
Protocol	Support Gmail/GOOGLE/QQ/EMAIL			
Onvif	Support Onvif			
S/N Ratio	≥ 58dB			
POE	Optional			
WIFI	NO			
Power Source	DC 12V/2A			
Consumption	<5W			
Operating Enviroment	-10℃~60℃ / 10% ~ 95%RH			
Working Humidity	≤90%			
Size(mm)	94mm x 69mm			
Weight(kg)	0.48 KG			