

Features:

- ◆ Waterproof IR Bullet IP Camera
- ◆ Waterproof level:IP66
- ◆ IR LED: 2 pcs, IR Range: 30M
- ◆ Obscured glass, hidden IR Led
- ◆ Video Output: 1 x RJ45 port, wifi Optional
- ◆ Support Onvif, Support Gmail/GOOGLE/QQ/EMAIL
- ◆ PNP(Plug and Play), support smart phone & tablets
- ◆ OSD, Motion Detection, Remote View and Control, IR-Cut
- ◆ Bracket Optional(add \$2)
- ◆ Working Temperature: -10℃~ +60℃
- ◆ Size: 160mm x 100mm x 110mm
- ◆ Weight: 900g



Specifications

Model ID	VN-JB10H	VN-JB13E	VN-JB20	VN-JB20F	VN-JB40	VN-JB50
Description	Waterproof Plastic IR Bullet IP Camera,Waterproof level:IP66, IR LED: 2 pcs, IR Range: 30M					
TV System	NTSC / PAL					
Video Output	1 x RJ45 port					
Chipset Solution	1/4" XM H42 + Hi3518E 1.0 Mega Pixels CMOS	1/3" Aptina AR0130 + Hi3518E 1.3 Mega Pixels CMOS	1/2.5" Sony IMX323 + Hi3516C 2 Mega Pixels CMOS	1/3" Aptina AR0237 + Hi3516D 2 Mega Pixels CMOS	1/3" OV4689 + Hi3516D 4MP HD CMOS Sensor	1/2.5" SONY IMX 178 5MP HD CMOS Sensor
Resolution	720P@ 25fps(PAL), 30fps(NTSC)	960P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	4MP @ 15fps(PAL), 15fps(NTSC)	5MP @ 15fps(PAL), 15fps(NTSC)
Effective Pixels	1920(H)×720(V)	1920(H)×960(V)	1920(H)×1080(V)	1920(H)×1080(V)	2592(H)×1520(V)	2592(H)×1944(V)
Minimum Illumination	0.001Lux					
Lens	3.6mm (2M Pixels)	3.6mm (3M Pixels)	3.6mm (3M Pixels)	3.6mm (3M Pixels)	3.6mm (3M Pixels)	3.6mm (5M Pixels)
	/	2.8/6/8mm (Optional)	2.8/6/8mm (Optional)	/	/	/
Sync, System	Internal Synchronization					
Network	1 RJ45 Ethernet interface, 10/100M adaptation					
Video Compression	H.264 compression			H.265 compression		
Protocol	Support Gmail/GOOGLE/QQ/EMAIL					
Onvif	Support Onvif					
S/N Ratio	≥ 58dB					
POE	Optional					
OSD	YES					
WIFI	/	/	/	/	Optional	Optional
Power Source	DC 12V/2A					
Consumption	<5W					
Operating Enviroment	-10℃~60℃ / 10% ~ 95%RH					
Working Humidity	≤90%					
Size(mm)	160mm x 100mm x 110mm					
Weight(kg)	0.9 kg					