

Features:

- ◆ 3" Metal IR Dome IP Camera Water Resistance: IP66
- ◆ IR LED: \varnothing 5 X 15pcs, IR Range: 20M
- ◆ Video Output: 1 x RJ45 port
- ◆ Support Onvif, Support Gmail/GOOGLE/QQ/EMAIL
- ◆ PNP(Plug and Play), support smart phone & tablets
- ◆ OSD, Motion Detection, Remote View and Control, IR-Cut
- ◆ Working Temperature: $-10^{\circ}\text{C} \sim +60^{\circ}\text{C}$, APP:Guard Viewer
- ◆ 24PCS Per Carton
- ◆ Size: 105mm x85mm
- ◆ Weight: 450g



Specifications

Model ID	VN-IGB20MG	VN-IGB20XG	VN-IGB20FG	VN-IGB20TG	VN-IGB30SG
Description	3" Metal IR Dome IP Camera, Water Resistance: IP66, IR LED: \varnothing 5 X 15 pcs, IR Range: 20M				
TV System	NTSC / PAL				
Video Output	1 x RJ45 port				
Chipset Solution	SC2232+MS313EY	IMX307+MS313EY	F23+MS316DC	IMX307+MS316DC	SC3235+Hi3516EV200
Resolution	1080P@ 25fps(PAL), 30fps(NTSC)	1080P@ 25fps(PAL), 30fps(NTSC)	1080P@ 25fps(PAL), 30fps(NTSC)	1080P@ 25fps(PAL), 30fps(NTSC)	1080P@ 25fps(PAL), 30fps(NTSC)
Effective Pixels	1920(H)x1080(V)	1920(H)x1080(V)	1920(H)x1080(V)	1920(H)x1080(V)	2048(H)x1536(V)
Minimum Illumination	0.001Lux				
Lens	3.6mm(5M Pixels) / 2.8mm(Optional)				
Sync, System	Internal Synchronization				
Network	1 RJ45 Ethernet interface, 10/100M adaptation				
Video Compression	H.265 compression				
Protocol	Support Gmail/GOOGLE/QQ/EMAIL				
Onvif	Support				
S/N Ratio	\geq 58dB				
POE	External PoE (Optional)				
Other features	Smart algorithm, Multiple image modes, Intelligent Identification				
Power Source	DC 12V/2A				
Consumption	<5W				
Operating Environment	$-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ / 10% ~ 95%RH				
Working Humidity	\leq 90%				
Size(mm)	105mm x85mm				
Weight(kg)	0.45 kg				
Vandsec Electronics Limited http://www.vandsec.com Email: info@vandsec.com					