

Features:

- ◆ PIR style Spy Camera
- ◆ IR LED: 14μX 18pcs, Invisible IR LED, IR Range: 15M
- ◆ Microphone Built-in Audio Output
- ◆ 60PCS Per Carton
- ◆ Size: 60mm x 104mm x 33mm
- ◆ Weight: 160g



Specifications

Model ID	VS-EB20FHD	VS-EB20ZHD	VS-EB20THD	VS-EB50KHD	VS-EB50SHD
Description	PIR style Spy Camera,IR LED: 14μX 18pcs, Invisible IR LED, IR Range: 15M				
TV System	NTSC / PAL				
Video Out	BNC 4 in 1(AHD, TVI, CVI, CVBS)				
	Main menu Switch TVI/CVI/AHD/CVBS output, OSD Switch TVI/CVI/AHD/CVBS output				
Chipset Solution	1/3" 1080P 2MP CMOS Sensor Low illum F37 + XM330	1/2.7" 1080P 2MP CMOS Sensor Low illum F33 + FH8536E	1/2.8" 1080P(2.13MP) STARVIS CMOS Sensor, Low illum, SONY IMX307 + NVP2441H	1/2.7" 5MP CMOS Sensor, Low illum Silicon K05 + FH8538M	1/2.9" 5MP CMOS Sensor Low illum, SONY IMX335 + FH8558M
Resolution	1080P@ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	5MP @ 25fps(PAL), 30fps(NTSC)	5MP @ 25fps(PAL), 30fps(NTSC)
Effective Pixels	1920(H)×1080(V)	1920(H)×1080(V)	1920(H)×1080(V)	2592(H)×1944(V)	2592(H)×1944(V)
Minimum Illumination	0.001Lux				
Lens	3.7mm Taper Pinhole Lens				
Sync, System	Internal Synchronization				
Scanning System	2:1 Interface				
Shutter Speed	1/60~1/100,000sec (N), 1/50~1/100,000sec (P)				
S/N Ratio	≥ 58dB				
Audio	Input / Output				
DWDR	YES(3D-NR)				
OSD	NO	Optional	YES	YES	YES
UTC	YES	YES	NO	YES	YES
Power Source	DC12V ±10%				
Consumption	<5W				
Operating Enviroment	-20℃~60℃ / 10% ~ 95%RH				
Working Humidity	≤90%				
Size(mm)	60mm x 104mm x 33mm				
Weight(kg)	0.16 kg				