

Features:

- ◆ 4" Medium Speed Mini PTZ Camera
- ◆ IR Led: 3pcs, IR Range: 40M
- ◆ Pan Range: 360°, Pan Speed: Max 80°/sec
- ◆ Tilt Range: 90°, Tilt Speed: Max 80°/sec
- ◆ Support Onvif, Preset: 255
- ◆ Pelco-P/D (Auto recognition)
- ◆ lightning-proof, surge-proof
- ◆ 4 Patrol track, 8 Cruise Track
- ◆ Working Temperature: -10°C~ +60°C
- ◆ Power Supply: DC 12V/1.5A
- ◆ Size: 185mm × 185mm × 240mm
- ◆ Weight: 3.8 KG



Specification:

MODEL NO.	VNP-FMV4X20HD	VNP-FMV4X50HD
Description	4" Medium Speed Mini PTZ Camera; IR Led: 3pcs, IR Range: 40M	
TV System	NTSC / PAL	
Image Sensor	1/3" CMOS 2.0 Mega Low Illumination HI3516E+SONY307 Starlight	1/3" CMOS 5.0 Mega Low Illumination HI3516D+5521
Resolution	1080P	1080P
Effective Pixels	1920(H) × 1080(V)	2592(H)×1944(V)
Lens	4X Optical Zoom (2.8-12mm Lens)	4X Optical Zoom (2.8-12mm Lens)
Minimum illumination	0.01Lux @(F1.6,AGC ON) ,0 Lux with IR	
Video interface	RJ45	
Video compression	H.264	H.265
Signal model	50HZ:25fps(1280 X 960) 60HZ:30fps(1280 X 960)	
Video bit rate	32kbps-16Mbps	
Day and night conversion	IR-Cut	
PTZ Control	RS485/PTZ keyboard controller	
Electronic shutter	1/25s ~ 1/100000s	
D-WDR	Support	
DNR	2D/3D-DNR	
Image direction	Mirror/ Flip	
Privacy zone	Support	
Mobile detection	Support	
Horizontal range	0°~360°	
Vertical range	0°~90°	
Horizontal speed	0.5°~15°/ s	
Vertical speed	0.5°~15°/ s	
Presets	255	
Cruise track	8 groups, each group for 16 presets	
Patrol track	4 groups, each group record 3 mins	
Audio I/O	Optional	
Audio compression	G.711A	
Alarm I/O	Optional	
POE	Built-in POE (Optional)	
ONVIF	Support	
Waterproof level	IP66	
Bracket	Wall mounted	
Size	185mm × 185mm × 240mm	
Weight	3.8 kg	
Power	DC12V/2A	
Work temperature	-30°C~60°C	