Al IP Camera

Model: VN-DB01		Product Features
		• Easy to install and use
		Clear and smooth video browsing; intelligent transmission giving full play to capabilities of the network
		Online firmware upgrade, and synchronous updating of the functions and experience
		Two-way voice intercom supported; echo eliminated; noise suppressed
tens		Compatible with Android; remote real-time monitoring supported with the IOS intelligent terminal
		4-megapixel starlight high resolution (2560X1440) for clear picture quality
		Dual-source lighting for night vision (night vision distance = 7 m) comprising infrared lamp / white-light source; color images available for night vision.
		The built-in rechargeable lithium battery with long battery life functions for up to 6 months under normal circumstances and can stand by for 12 months
		2 2 4G Wi-Fi supported (IEEE802.11b/g/n)
		Cloud storage, Micro SD card (up to 128GB) and mobile phone video recording supported
		QR code intelligent connection and network allocation supported
		Qrc code intelligent connection and network anotation supported Supporting human contour detection, activity zone, vechicle detection, pet snapshot and package inspection (value added service required)
		1P65 Easy installation: support 1/4 universal screw bracket and magnetic suction bracket Specifications
Master Pro		Specifications
Master Processor	SOC	ARM
Image Sensor	Sensor	1/3° color CMOS Sensor
	Lens	M12, f: 2.97mm, F1.6, 4-megapixel
	Visual angle	H (horizontal) 105 degrees; V (vertical) 58.3 degrees; D (diagonal) 123.6 degrees
		0.01 Lux
Audio	Input/Output	Two-way voice intercom available (built-in Microphone and speaker)
	Audio Compressing Method	AAC
Video	Video Compressing Method	H.265
	Lighting Frequency	50Hz, 60Hz
	Image Frame Rate	15 fps
	Maximum Image Resolution	2K/3MP(2048*1536)
	Light Source for Night Vision	Mid-power infrared lamp (850nm in wavelength) / dual-source white-light source with an irradiation distance of 7m
Network	Wireless Network	24G Wi-Fi (IEEE802.11b/g/n), built-in antenna
	Protocols Supported	TCP/IP, UDP/IP, DHCP, RTMP, MUTP
	IP Address Supported	Dynamic IP address supported
AI	Intelligent Features	Human contour detection, activity zone, vechicle detection, pet snapshot and package inspection
Alarm Notification	Alarm Methods	Alarm push by mobile APP, white light flashing and alarm sound
Wake-up	Wake-up Method	PIR body induction wake-up, and remote wake-up
Video Recording	Recording Method	Alarm triggered recording, and manual recording
	Video Storage	Cloud storage, local Micro SD card, and mobile phone memory
Indicator Lamps	LED Indicator	RGB tri-color lamp indicating the status of power/network signal/functionality
Battery	Capacity	900mAh
	Removability	Unremovable
	Battery Life	6 months (provided that 20 10s videos are recorded per day)
	Standby Time	1 year
	Charging Voltage	DV 5V+-5%/1.5A
	Charge Time	Within 10 hours
	Protection Method	IP65 is dustproof and waterproof, over-current/over-discharge/over-charge/short circuit/charging protection at high & low temperatures
Power Consumption Interfaces	Standby Power Consumption	1903 is up quoti and waterproof, over-current/over-uscharge/over-charge/short circul/charging protection at high & low temperatures
	Power Consumption of Daytime Operation	1.151mW (44 0.46mA) 1.11W (3.87V 288mA)
	Power Consumption of Operation at Night	2.02W (3.73V 542mA)
		2.02W (3.73V 54.211R) 1 Micro USB interface
	Power Supply	
	SD Card	1 Micro SD card (up to 128GB supported)
Installation	Keys	1 reboot key and 1 on/off key
Method	Installation Method	Magnet and 1/4 universal screw holes
	Dustproof and waterproof	IP65
Environment	Operating Environment	-10° ~ 45°C /10% ~ 80% (no condensation)
	Storage Environment	-20°C ~ 60° /0% ~ 90% (no condensation)
Specifications	Size (LxWxH)	64(L)mm x 73(W)mm x 98mm(H)
	Material + Process	ABS+PC
	Color	White with high gloss
Certifications	Certificate	CEROHS,FCC, UN38.3