

Features:

- ◆ 3" Plastic IR Dome Camera
- ◆ IR LED: 14μX12pcs, IR Range: 20M
- ◆ 50PCS Per Carton
- ◆ Size: 92mm x 78mm
- ◆ Weight: 300g



Specifications

Model ID	VD-IOB20MHD	VD-IOB20FHD	VD-IOB20ZHD	VD-IOB20THD	VD-IOB50KHD	VD-IOB50SHD	VD-IOB80CHD	VD-IOB80VHD
Description	3" Plastic IR Dome Camera, IR LED: 14μX12pcs, IR Range: 20M							
TV System	NTSC / PAL							
Video Out	BNC 4 in 1(AHD, TVI, CVI, CVBS)							
	Main menu Switch TVI/CVI/AHD/CVBS output / OSD Switch TVI/CVI/AHD/CVBS output							
Chipset Solution	1/4" 1080P 2MP CMOS Sensor, Low illum M125 + XM330	1/3" 1080P 2MP CMOS Sensor, low illum F37 + XM330	1/2.7" 1080P 2MP CMOS Sensor Low illum F33 + FH8536E	1/2.8" 1080P 2MP STARVIS CMOS Sensor, Low illum SONY IMX307 + NVP2441H	1/2.7" 5MP CMOS Sensor Low illum Silicon K05 + FH8538M	1/2.9" 5MP CMOS Sensor Low illumination SONY IMX335 + FH8558M	1/2.5" 4K(8MP) CMOS Sensor Low illum C08 + FH8556	1/2.3" 4K(8MP) CMOS Sensor, Low illumination, OV12895 + NVP2481
Resolution	1080P	1080P	1080P	1080P	5MP	5MP	4K(8MP)	4K(8MP)
Effective Pixels	1920(H)×1080(V)	1920(H)×1080(V)	1920(H)×1080(V)	1920(H)×1080(V)	2592(H)×1944(V)	2592(H)×1944(V)	3840(H)×2160(V)	3840(H)×2160(V)
Minimum Illumination	0.001Lux							
Lens	3.6mm Board Lens(2.8/6/8mm Optional)						F1.0 4mm 4K Lens	
Sync, System	Internal Synchronization							
Scanning System	2:1 Interface							
Shutter Speed	1/60~1/100,000sec (N), 1/50~1/100,000sec (P)							
S/N Ratio	≥ 58dB							
DWDR	NO	NO	YES	YES	YES	YES	YES	YES
DNR	NO	NO	YES(3D-NR)	YES(3D-NR)	YES(3D-NR)	YES(3D-NR)	YES(3D-NR)	YES(3D-NR)
OSD	NO	NO	Optional	YES	YES	YES	YES	YES
UTC	YES	YES	YES	YES	YES	YES	YES	YES
Power Source	DC12V ±10%							
Consumption	<5W							
Operating Environment	-20℃~60℃ / 10%~95%RH							
Working Humidity	≤90%							
Size(mm)	92mm x 78mm							
Weight(kg)	0.30 kg							