

Features:

- ◆ 6" IP66 Medium Speed IR PTZ Dome
- ◆ IR Led: 8pcs, IR Range: 150M
- ◆ Pan Range: 355°, Pan Speed: Max 90°/sec
- ◆ Tilt Range: 90°, Tilt Speed: Max 90°/sec, Preset: 128
- ◆ Support HD-TVI/HD-CVI/AHD/CVBS HD Video Output
- ◆ Pelco-P/D (Auto recognition)
- ◆ lightning-proof, surge-proof
- ◆ 4 Patrol track, 4 Cruise Track
- ◆ Working Temperature: -10°C~ +60°C
- ◆ Power Supply: DC 12V include
- ◆ Size: 230mm x 230mm x 380mm
- ◆ Weight: 6.8KG



Specification:

| MODEL NO. | VP-IMV20X20HD | VP-IMV20X50HD | VP-IMV33X50HD |
|---|---|---|---|
| Description | 6" IP66 Medium Speed IR PTZ Dome;IR Led: 8pcs, IR Range: 150M | | |
| TV System | NTSC / PAL | | |
| Image Sensor | 1/3" 2.0 MP SONY IMX307 + NVP2441H CMOS, Low Illumination | 1/3" 5.0 MP SONY IMX335 + 2477 CMOS, Low Illumination | 1/3" 5.0 MP SONY IMX335 + 2477 CMOS, Low Illumination |
| Resolution | 1080P | 5MP | 5MP |
| Effective Pixels | 1920(H) × 1080(V) | 2592(H)×1944(V) | 2592(H)×1944(V) |
| Lens | 20x Optical Zoom (4.7-84.6mm Lens) | 20x Optical Zoom (4.7-84.6mm Lens) | 33x Optical Zoom (4.6-152mm Lens) |
| Minimum illumination | 0.01Lux @(F1.6,AGC ON) ,0 Lux with IR | | |
| Video interface | BNC | | |
| Video bit rate | 32kbps-16Mbps | | |
| Day and night conversion | IR-Cut | | |
| PTZ Control | RS485/PTZ keyboard controller | | |
| Electronic shutter | 1/25s ~ 1/100000s | | |
| D-WDR | Support | | |
| DNR | 2D/3D-DNR | | |
| Image direction | Mirror/ Flip | | |
| Privacy zone | Support | | |
| Mobile detection | Support | | |
| Horizontal range | 0°~355° | | |
| Vertical range | 0°~90° | | |
| Horizontal speed | 30°/ s | | |
| Vertical speed | 30°/ s | | |
| Presets | 128 | | |
| Cruise track | yes | | |
| Patrol track | yes | | |
| Audio I/O | Optional | | |
| Waterproof level | IP66 | | |
| Bracket | Wall mounted | | |
| Size | 230mm x 230mm x 380mm | | |
| Weight | 6.8 kg | | |
| Power | DC12V | | |
| Work temperature | -30°C~60°C | | |
| Vandsec Electronics Limited http://www.vandsec.com Email: info@vandsec.com | | | |