

Features:

- ◆ 7" Waterproof Metal IP66 4G IP High Speed PTZ Camera
- ◆ Pan Range: 360°, Pan Speed: Max 180°/sec
- ◆ Tilt Range: 90°, Tilt Speed: Max 180°/sec
- ◆ 8pcs IR Array Led, IR Range: 100M
- ◆ TF Card local Storage (Max.128G,over 32GB need FAT32 Format)
- ◆ Support 3G/4G small Sim card (America or Japan 4G add \$5)
- ◆ PNP(Plug and Play), support smart phone & tablets
- ◆ Preset: 128, App (camhipro)
- ◆ Video Compression: H.265 Main Profile; MJPEG/JPEG Baseline
- ◆ Working Temperature: -10℃~ +60℃
- ◆ Size: 230mm x 230mm x 380mm
- ◆ Power: 12V power adapter include
- ◆ Weight: 6.8KG



Specifications:

Model	VN-GBN22X20-G	VN-GBN22X50-G	VN-GBN30X20-G
Description	7" Waterproof IP66 4G IP High Speed PTZ Camera,8pcs IR Array Led, IR Range: 100M		
TV System	NTSC / PAL		
Connection method	3G/4G		
Resolution	2.0 MegaPixels CMOS GK7205V200+SC2335 1080P@ 25fps(PAL), 30fps(NTSC)	5.0 MegaPixels CMOS GK7205V300+IMX335 5MP@ 25fps(PAL), 30fps(NTSC)	2.0 MegaPixels CMOS GK7205V200+SC2335 1080P@25fps(PAL), 30fps(NTSC)
Effective Pixels	1920(H) × 1080(V)	2560(H) × 1920(V)	1920(H)×1080(V)
Lens	22x Optical Zoom(4.7-103.4mm)		30x Optical Zoom(4.7-141mm)
Minimum Illumination	0.001Lux		
Day/Night	IR cut filter with auto switch, IR sensor		
Network	10/100M adaptation ,3G/4G Network signal		
Video Compression	H.265 compression		
Audio processing	G.711A decoding standard, Audio Optional		
TF Card	Max.128G,over 32GB need FAT32 Format		
Pan Range	0°-355°		
Tilt Range	0°-90°		
Pan Speed	Max180°/sec		
Tilt Speed	Max180°/sec		
Preset	128		
Power/Current	12V power adapter include		
Consumption	5.0W		
Size	230mm x 230mm x 380mm		
Weight (g)	6.8 kg		
Temperature	-10℃~+60℃		
Humidity	0%-90%		
Vandsec Electronics Limited http://www.vandsec.com Email: info@vandsec.com			