


## Features:

- ◆ 8'' Waterproof Metal IP66 4G IP High Speed PTZ Camera
- ◆ Pan Range: 355° , Pan Speed: Max 90° /sec
- ◆ Tilt Range: 90° , Tilt Speed: Max 90° /sec
- ◆ IR & White LED: 12pcs, IR Range: 100M
- ◆ Support TF Card upto 128G, 3G/4G small Sim card(America or Japan 4G add \$5)
- ◆ PNP(Plug and Play), support Human detect, support smart phone & tablets
- ◆ H.265 video compression, video Push, QR Scan or download app (camhipro)
- ◆ Preset: 128, Wifi connect by scan QR codes, smart key easily, radar scanning
- ◆ Red and blue light alert, Push alarm to smart phone
- ◆ Working Temperature: -10℃~ +60℃
- ◆ Size: 210mm x 370mm x 400mm
- ◆ Power: 12V power adapter include
- ◆ Weight: 7.8KG



## Specifications:

Model	VN-GBW18X20-G	VN-GBW18X50-G	VN-GBW18X80-G	VN-GBW30X50-G	VN-GBW30X80-G
Description	8'' Waterproof Metal IP66 4G IP High Speed PTZ Camera, IR & White LED: 12pcs, IR Range: 100M				
TV System	NTSC / PAL				
Connection method	3G/4G				
Resolution	2.0 Megapixel, T31L+GC2083 CMOS Sensor	5.0 Megapixel, T31X+SC5238 CMOS Sensor	8.0 Megapixel, SSC338Q+IMX415 CMOS Sensor	5.0 Megapixel, T31X+SC5238 CMOS Sensor	8.0 Megapixel, SSC338Q+IMX415 CMOS Sensor
Effective Pixels	1920(H) × 1080(V)	2560(H) × 1920(V)	3840(H) × 2160(V)	2560(H) × 1920(V)	3840(H) × 2160(V)
Lens	18x Optical Zoom(5.3-96mm Lens)	18x Optical Zoom(5.3-96mm Lens)	18x Optical Zoom(5.3-96mm Lens)	30x Optical Zoom(4.7-141mm Lens)	30x Optical Zoom(4.7-141mm Lens)
Minimum Illumination	0.001Lux				
Day/Night	IR cut filter with auto switch, IR sensor				
Network	10/100M adaptation ,3G/4G Network signal				
Video Compression	H.265 compression				
Audio processing	G.711A decoding standard, Audio Optional				
TF Card	Max.128G, over 32GB need FAT32 Format				
Pan Range	0° -355°				
Tilt Range	0° -90°				
Pan Speed	Max180° /sec				
Tilt Speed	Max180° /sec				
Preset	128				
Power/Current	12V power adapter include				
Consumption	20W				
Size	210mm x 370mm x 400mm				
Weight (g)	7.8 kg				
Temperature	-10℃~+60℃				
Humidity	0%-90%				
Vandsec Electronics Limited   <a href="http://www.vandsec.com">http://www.vandsec.com</a>   Email: <a href="mailto:info@vandsec.com">info@vandsec.com</a>					

	VN-GBN		备注	
产品	产品图片			<p style="color: red;">产品的重量芯片方案的不同有所差异，这些重量差异比较小，可以忽略不计。</p>
	产品尺寸 (单位CM)			
	产品重量 (单位KG)			
包装	包装尺寸 (单位CM)	长	26.5	
		宽	26	
		高	43.5	
	包装重量 (单位KG)	4.40		一整套重量(含配件)
	包装体积重 (单位CBM)	5.99		
装箱	装箱尺寸 (单位CM)	长	54.5	
		宽	27.5	
		高	45.5	
	装箱数量 (单位台)	2		
	装箱实重 (单位KG)	9.6		
	装箱体积重 (单位CBM)	13.64		

## 特征:

- ◆ 7寸高速4G无线迷你网络摄像机，防水等级：IP66
- ◆ 红外灯:8颗，红外距离：100米
- ◆ 支持WIFI/, 3G/4G SIM 中卡
- ◆ TF卡最大支持128G，超过32G需FAT32格式
- ◆ 支持邮件报警推送，APP(CamHi)
- ◆ 扫码智能连接WIFI，支持双向语音
- ◆ 支持智能手机，平板等设备
- ◆ 尺寸:185mm × 185mm × 240mm
- ◆ 重量：6.5 KG



型号	VN-GBN22X20	VN-GBN30X20
视频制式	NTSC / PAL	
视频输入	4G	
传感器	2.0 Megapixel CMOS Sensor	2.0 Megapixel CMOS Sensor
视频输出	1920 (H) x1080 (V)	1920 (H) x1080 (V)
镜头	22倍变焦 (4.7-103.4mm)	30倍变焦 (4.7-141mm)
最低照度	0.001Lux	
日夜转换模式	标配IR-cut	
视频压缩	H.264	
网络	1 RJ45 网络接口, 10/100M 传输, 3G/4G 网络信号	
内存卡	TF卡 (最大128, 超过32G需要FAT32格式)	
水平角度	0° -355°	
垂直角度	0° -90°	
水平速度	最大180° /秒	
垂直速度	最大180° /秒	
预置位	128个	
降噪	3D降噪	
宽动态	支持数字宽动态	
复位键接口	支持一键复位	
移动侦测	支持	
电源	12V/2000MA电源	
尺寸	185mm × 185mm × 240mm	
重量	6.5 kg	
工作温度	-10℃ ~ +60℃	
Vandsec Electronics Limited   <a href="http://www.vandsec.com">http://www.vandsec.com</a>   Email: <a href="mailto:info@vandsec.com">info@vandsec.com</a>		