


Features:

- ◆ 2.4G—Waterproof IR Bullet IP Camera and WIFI NVR
- ◆ P2P Cloud Service,Support Onvif
- ◆ 720P/ 960P /1080P HD Real-time
- ◆ Remote View & Control, Anywhere, anytime.
- ◆ Motion Detection with Email Alert
- ◆ Day & Night Monitoring with IR-cut Auto Switch
- ◆ Support Andriod Mobile, Tablets, iPhone, iPad.

Model Name	Contents
VK-N5108W10-W	VN-GB10 x 8pcs
	VN-N5108 x 1pc
VK-N5108W13-W	VN-GB13 x 8pcs
	VN-N5108 x 1pc
VK-N5108W20-W	VN-GB20 x 8pcs
	VN-N5108 x 1pc



Camera Specification

	2.4G Strong Wi-Fi signal, 5db Antenna WIFI Waterproof IR Bullet IP Camera;Waterproof level:IP66;IR LED: \varnothing 5X36pcs, IR Range: 20M		
Model	VN-GB10	VN-GB13	VN-GB20
TV System	NTSC / PAL		
Video Out	Ethernet cable		
Chipset Solution	1/4" OV 9712+Hi3518E 1.0 Mega Pixels CMOS	1/3" Aptina AR0130 + Hi3518E 1.3 Mega Pixels CMOS	1/2.5" Sony IMX323 + Hi3516C 2 Mega Pixels CMOS
Resolution	720P @ 25fps(PAL), 30fps(NTSC)	960P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)
Effective Pixels	1920(H) \times 720(V)	1920(H) \times 960(V)	1920(H) \times 1080(V)
Minimum Illumination	0.001Lux		
Lens	3.6mm Board Lens		
Sync, System	Internal Synchronization		
Network	1 RJ45 Ethernet interface, 10/100M adaptation		
Video Compression	H.264 compression		
Onvif	YES		
S/N Ratio	\geq 58dB		
Protocol	Support Gmail/GOOGLE/QQ/EMAIL		
OSD	YES		
POE	YES		
WIFI	YES		
Power Source	DC 12V/1A		
Consumption	<5W		
Operating Enviroment	-20 $^{\circ}$ C~60 $^{\circ}$ C / 10% ~ 95%RH		
Working Humidity	\leq 90%		
Size(mm)	92mm x 62mm x 58mm		
Weight(kg)	0.6 kg		

DVR Specification



H.264 WIFI NVR
2.4G Strong Wi-Fi signal, 5db Antenna

Model		VN-N5108
System	Main Processor	Hi3531D
	Operation System	LINUX, Compression Mode: H.264
Video	Video Input	8CH
	Video Output	1 x VGA / 1 x HDMI (1920*1080)
	Video Distance	Ethernet cable
Audio	Audio Input	N/A
	Audio Output	N/A
Recording	Recording Channel	8CH × 720P;720P: 1920 × 720 at 30 Fps(NTSC), 25 Fps(PAL) 8CH × 960P;960P: 1920 × 960 at 30 Fps(NTSC), 25 Fps(PAL) 8CH × 1080P;1080P: 1920 × 1080 at 30 Fps(NTSC), 25 Fps(PAL)
	Resolution	720P/960P/1080P
	Frame Rate	30 Fps(NTSC), 25 Fps(PAL)
	Recording Mode	Realtime Video Recording
Playback	Playback Channel	4CH x 720P/ 4CH x 960P/ 2 x 1080P
	Search Mode	Time, Date, Motion Detection, Exact Search
	Playback Mode	Normal Play / Fast Forward / Fast Rewind / Frame by Frame
Alarm	Alarm Input	N/A
	Alarm Output	N/A
Storage	HDD Interface	1 x SATA Fixed HDD
	Capability	SATA HDD up to 6TB each
Backup	USB Disk	2 x USB 2.0 port
	Backup Format	H.264 (only for Playback Software - General H.264 Player V1.7.0.)
	Backup Mode	Network download / Flash USB / movable HDD/SATA HDD / DVD-RW
PTZ	PTZ	R485 control
Network	Interface	RJ45 port / 10M / 100M / 1,000Mbps Ethernet
	Protocol	TCP/IP, DHCP, DDNS, DNS, PPPoE, UPNP, NTP, SMTP
	Mobile phone Support	mobile view app Smart meye (iPhone, Android)
	Compatible Browser	iCloud Software, one-click online; Support IE, Firefox, Google Chrome
	Computer System Support	Windows 2000, XP, Vista, 7, 8 / Mac OS x 10.6/10.7
	Free DDNS	iCloud Free DDNS Server (P2P function)
	IP Camera Protocol	ONVIF Version Platform Protocol (Digital Menu)
Others	Simultaneous Remote Viewers	6 Users Online
	Operating Temperature	0°C ~ 55°C
	Operating Humidity	10% ~ 90%
	Dimension	211mm×200mm×40mm
	Net Weight	2.5 KG
	HDD Screw	4 PCS (1 Pack)
	Accessories	USB Mouse ×1PC/User Manual ×1PC/ Power Supply × 1PC/ Client software CD ×1PC
Power Supply	DC12V/2A Power Adapter	